

In the Specification

Page, 14, change the following paragraph to read as follows:

--[0037] Figure 2 is a perspective view of an exemplary embodiment of an exemplary embodiment of the present invention.--

Cancel pages 17-20.

Page 22, change the following paragraph to read as follows:

--[0053] A second end cap 50 seals the tube second end 34. A swivel loop 52 is attached to the second end cap and a clip hook 54 is attached to the swivel loop. A loop 56 is attached to the tube proximate the second end, through which a fastener strap 58 is threaded. The fastener strap has a first hook-and-loop portion end 60 and a second hook-and-loop portion end 62 for joining the strap 58 ~~[[44]]~~ about various objects.--

Pages 22-23, change the following paragraph to read as follows:

--[0055] The control assembly 76 is attached to the elongated member and adapted for receiving electric power from the portable electric power source, in this embodiment, a battery 78, as shown in Figure 6. As shown in Figure 3, the control assembly also includes a flasher unit 80, a switch 82 for turning the lights 72 on and off, and a flasher unit control button 84 for a flasher unit. Using conventional technology, the control assembly provides light control functions including steady on, fast flash, slow flash, sequential lighting, and twinkle.--

Page 24, change the following paragraph to read as follows:

--[0059] Turning now to Figure 9, an exemplary embodiment of the device 20 is illustrated wherein the user 21 has placed a pair of the devices 20 along her upper torso 23 in suspender fashion, with the clip hooks 40 and similar hooks on the opposite side of user (not shown) 40,54 being attached to the user's belt.--